



# County of Fresno

DEPARTMENT OF PUBLIC WORKS AND PLANNING  
STEVEN E. WHITE, DIRECTOR

June 27, 2025

Contract No. 25-04-PR

**ADDENDUM NO. 1** to KEARNEY PARK IMPROVEMENTS, revising the Bidding and Contract Documents/Plans/Bid Opening as follows:

## **TABLE OF CONTENTS**

No changes

## **NOTICE TO BIDDERS**

No changes

## **BID ITEMS AND APPLICABLE SECTIONS**

No changes

## **SPECIAL PROVISIONS**

No changes

## **TECHNICAL SPECIFICATIONS**

*Removed restroom and shelter procurement instructions to contractor as they are County furnished.*

Section 01 25 00 Substitution Procedures  
Part 2 - PRODUCTS

### **DELETE:**

- C. Public Interest Findings: The Department has made a public interest finding and has determined that the following items shall be used for the project, and no substitution therefor shall be allowed:
1. CXT Incorporated Prefabricated Public Restroom Model# S-301 "Santiago"
  2. ICON Shelter Systems Incorporated 30' x 40' x 8.5' Rectangular Gable Shelter

## **FEDERAL & STATE REQUIREMENTS**

No changes

## **PROJECT DETAILS / DRAWINGS**

No changes

## **PROPOSAL/BID BOOK: PAPER**

No changes

## **PROPOSAL/BID BOOK: BID EXPRESS**

No changes

## **AGREEMENT**

### **DELETE:**

**ARTICLE V.** To the fullest extent permitted by law with respect to any work required to be done under this Contract, the Contractor will indemnify and hold harmless the Owner, Borelli & Associates, Inc., and all other participating public agencies, whether or not said agencies are named herein, who have jurisdiction within the areas in which the work is to be performed, and all officers and employees of the Owner, the State, the United States and said other participating agencies, from any and all costs and expenses, attorney fees and court costs, damages, liabilities, claims and losses occurring or resulting to Owner in connection with the performance, or failure to perform, by Contractor, its officers, agents or employees under this Agreement and the Contract, and from any and all costs and expenses, attorney fees and court costs, damages, liabilities, claims and losses occurring or resulting to any person, firm or corporation who may be injured or damaged by the performance, or failure to perform, of Contractor, its officers, agents or employees under this Agreement and the Contract.

### **REPLACE with:**

**ARTICLE V.** To the fullest extent permitted by law with respect to any work required to be done under this Contract, the Contractor will indemnify and hold harmless the Owner, State of California, Borelli & Associates, Inc., and all other participating public agencies, whether or not said agencies are named herein, who have jurisdiction within the areas in which the work is to be performed, and all officers and employees of the Owner, the State, the United States and said other participating agencies, from any and all costs and expenses, attorney fees and court costs, damages, liabilities, claims and losses occurring or resulting to Owner in connection with the performance, or failure to perform, by Contractor, its officers, agents or employees under this Agreement and the Contract, and from any and all costs and expenses, attorney fees and court costs, damages, liabilities, claims and losses occurring or resulting to any person, firm or corporation who may be injured or damaged by the performance, or failure to perform, of Contractor, its officers, agents or employees under this Agreement and the Contract.

## **PLANS**

**DELETE:** Sheet No. E1.04

**REPLACE with:** Sheet No. E1.04A

## **END OF ADDENDUM NO. 1**

-----  
Please attach this Addendum to the inside cover of the Specifications booklet. If you have given the Bidding and Contract Documents to someone else, please forward this Addendum.  
-----



















6/27/25  
Date Signed



A handwritten signature in blue ink, appearing to read "Sebastian Artal", written over a horizontal line.

**Supervising Engineer:** \_\_\_\_\_

Sebastian Artal, PE C76724

FRESNO COUNTY  
**Department of Public Works and Planning**  
m/a 2220 Tulare Street, Suite 720  
Fresno, CA 93721-2106

LIGHTING FIXTURE SCHEDULE (#)						
TYPE	LIGHTS	MANUFACTURER AND MODEL	LAMPS	REMARKS	WATTS	LBS
E1		B-K LIGHTING #S-TY2-LED-X51-NFL-10-D57-RO	LED	5,571 LUMENS [NOMINAL] LED FIXTURE FLOOR MOUNTED. INSTALL SO IT AIMS TOWARD THE FLAG. LIGHT FIXTURE SHALL HAVE 0-10V DIMMING DRIVER.	57	26
E2		EVERGREEN #104340L-40LED-3000K-DIM	LED	4,000 LUMEN, LED FIXTURE WET RATED. LIGHT FIXTURE SHALL HAVE 0-10V DIMMING DRIVER.	40	20
S1		COOPER OR EQUAL GARDCO ECOFORM #GLEON-SA1B-740-U-T3-EA-AHD145	LED	5,986 LUMENS, POLE MOUNTED LED FIXTURE. FIXTURE SHALL BE MOUNTED ON A 25-FOOT HIGH, 5-INCH SQUARE STEEL POLE. FIXTURE SHALL HAVE AFTER HOURS DIMMING OPTION CAPABLE OF TWO NIGHTTIME MODES WITH AT LEAST 50% DIMMING. LIGHT FIXTURE SHALL HAVE PHOTOCELL.	44	33
S2		COOPER OR EQUAL GARDCO ECOFORM #GLEON-SA1B-740-U-T4FT-EA-AHD145 (2) LIGHT FIXTURES AT 90 DEGREES APART	LED	(2) 5,986 LUMENS, POLE MOUNTED LED FIXTURE AT 90 DEGREES APART. FIXTURES SHALL BE MOUNTED ON A 25-FOOT HIGH, 5-INCH SQUARE STEEL POLE. FIXTURES SHALL HAVE AFTER HOURS DIMMING OPTION CAPABLE OF TWO NIGHTTIME MODES WITH AT LEAST 50% DIMMING. LIGHT FIXTURES SHALL HAVE PHOTOCELL.	TWO LIGHT FIXTURES 44W EACH	TWO LIGHT FIXTURES 33 LBS EACH
S3		COOPER OR EQUAL GARDCO ECOFORM #GLEON-SA1B-740-U-T4FT-EA-AHD145 (3) LIGHT FIXTURES AT 90 DEGREES APART	LED	(3) 6,019 LUMENS, POLE MOUNTED LED FIXTURES AT 90 DEGREES APART. FIXTURES SHALL BE MOUNTED ON A 25-FOOT HIGH, 5-INCH SQUARE STEEL POLE. FIXTURES SHALL HAVE AFTER HOURS DIMMING OPTION CAPABLE OF TWO NIGHTTIME MODES WITH AT LEAST 50% DIMMING. LIGHT FIXTURES SHALL HAVE PHOTOCELL.	THREE LIGHT FIXTURES 44W EACH	THREE LIGHT FIXTURES 33 LBS EACH
S4		COOPER OR EQUAL GARDCO ECOFORM #GLEON-SA1B-740-U-T4FT-EA-AHD145 (2) LIGHT FIXTURES AT 180 DEGREES APART	LED	(2) 6,019 LUMENS, POLE MOUNTED LED FIXTURES AT 180 DEGREES APART. FIXTURES SHALL BE MOUNTED ON A 25-FOOT HIGH, 5-INCH SQUARE STEEL POLE. FIXTURES SHALL HAVE AFTER HOURS DIMMING OPTION CAPABLE OF TWO NIGHTTIME MODES WITH AT LEAST 50% DIMMING. LIGHT FIXTURES SHALL HAVE PHOTOCELL.	TWO LIGHT FIXTURES 44W EACH	TWO LIGHT FIXTURES 33 LBS EACH
S5		COOPER OR EQUAL GARDCO ECOFORM #GLEON-SA6B-740-U-T4FT-EA-AHD145	LED	34,384 LUMENS, POLE MOUNTED LED FIXTURE. FIXTURE SHALL BE MOUNTED ON A 25-FOOT HIGH, 5-INCH SQUARE STEEL POLE. FIXTURE SHALL HAVE AFTER HOURS DIMMING OPTION CAPABLE OF TWO NIGHTTIME MODES WITH AT LEAST 50% DIMMING. LIGHT FIXTURE SHALL HAVE PHOTOCELL.	249	44
S6		COOPER OR EQUAL GARDCO ECOFORM #GLEON-SA6B-740-U-T4FT-EA-AHD145-MS/DIM-L40W	LED	34,384 LUMENS, POLE MOUNTED LED FIXTURE. FIXTURE SHALL BE MOUNTED ON A 25-FOOT HIGH, 5-INCH SQUARE STEEL POLE. FIXTURE SHALL HAVE AFTER HOURS DIMMING OPTION CAPABLE OF TWO NIGHTTIME MODES WITH AT LEAST 50% DIMMING AND WITH MOTION RESPONSE OVERRIDE DURING THE PROGRAMMED 50% DIMMED PERIOD. LIGHT FIXTURE SHALL HAVE PHOTOCELL.	249	44
S7		COOPER OR EQUAL GARDCO ECOFORM #GAN-SA1B-740-U-T4FT-ADJS-AHD145-MA1197-XX	LED	(3) 6,019 LUMENS, POLE MOUNTED FLOOD LED FIXTURES. FIXTURES SHALL BE TENON MOUNTED ON A 25-FOOT HIGH, 5-INCH SQUARE STEEL POLE AT 120 DEGREES. FIXTURES SHALL HAVE AFTER HOURS DIMMING OPTION CAPABLE OF TWO NIGHTTIME MODES WITH AT LEAST 50% DIMMING. LIGHT FIXTURE SHALL HAVE PHOTOCELL. LIGHT FIXTURE SHALL BE MOUNTED AT 45 DEGREES FROM HORIZONTAL. REFER TO PLANS FOR AIMING REQUIREMENT.	THREE LIGHT FIXTURES 44W EACH	THREE LIGHT FIXTURES 34 LBS EACH
S8		COOPER OR EQUAL GARDCO ECOFORM #GAN-SA1B-740-U-T4FT-ADJS-AHD145-MA1037-XX	LED	(2) 6,019 LUMENS, POLE MOUNTED FLOOD LED FIXTURES. FIXTURES SHALL BE TENON MOUNTED ON A 25-FOOT HIGH, 5-INCH SQUARE STEEL POLE AT 180 DEGREES. FIXTURES SHALL HAVE AFTER HOURS DIMMING OPTION CAPABLE OF TWO NIGHTTIME MODES WITH AT LEAST 50% DIMMING. LIGHT FIXTURE SHALL HAVE PHOTOCELL. LIGHT FIXTURE SHALL BE MOUNTED AT 30 DEGREES FROM HORIZONTAL.	TWO LIGHT FIXTURES 44W EACH	TWO LIGHT FIXTURES 34 LBS EACH
S9		COOPER OR EQUAL GARDCO ECOFORM #GAN-SA6B-740-U-T4FT-ADJS-AHD145-MA1036-XX	LED	34,384 LUMENS, POLE MOUNTED FLOOD LED FIXTURE. FIXTURE SHALL BE TENON MOUNTED ON A 25-FOOT HIGH, 5-INCH SQUARE STEEL. FIXTURE SHALL HAVE AFTER HOURS DIMMING OPTION CAPABLE OF TWO NIGHTTIME MODES WITH AT LEAST 50% DIMMING. LIGHT FIXTURE SHALL HAVE PHOTOCELL. LIGHT FIXTURE SHALL BE MOUNTED AT 45 DEGREES FROM HORIZONTAL AND AIM TOWARDS THE PERFORMANCE STAGE AREA.	249	45
S10		COOPER OR EQUAL GARDCO ECOFORM #GAN-SA6B-740-U-T4FT-ADJS-AHD145-MS/DIM-L40W	LED	34,384 LUMENS, POLE MOUNTED FLOOD LED FIXTURE. FIXTURE SHALL BE TENON MOUNTED ON EXISTING ROUND POLE. FIXTURE SHALL HAVE AFTER HOURS DIMMING OPTION CAPABLE OF TWO NIGHTTIME MODES WITH AT LEAST 50% DIMMING. LIGHT FIXTURE SHALL HAVE PHOTOCELL. LIGHT FIXTURE SHALL BE MOUNTED AT 45 DEGREES FROM HORIZONTAL AND AIM TOWARDS THE PERFORMANCE STAGE AREA.	249	45
S11		COOPER OR EQUAL GARDCO ECOFORM #GAN-SA1B-740-U-T4FT-ADJS-AHD145-MA1036-XX	LED	6,019 LUMENS, POLE MOUNTED FLOOD LED FIXTURE. FIXTURE SHALL BE TENON MOUNTED ON A 25-FOOT HIGH, 5-INCH SQUARE STEEL POLE AT 180 DEGREES. FIXTURE SHALL HAVE AFTER HOURS DIMMING OPTION CAPABLE OF TWO NIGHTTIME MODES WITH AT LEAST 50% DIMMING. LIGHT FIXTURE SHALL HAVE PHOTOCELL. LIGHT FIXTURE SHALL BE MOUNTED AT 30 DEGREES FROM HORIZONTAL.	44	34
S12		EVERGREEN #104340L-40LED-3000K-DIM POLE: MILLERBEND BEMIDJI #DBA-E-070-120-PT1-H	LED	4,000 LUMEN, LED FIXTURE WET RATED. FIXTURES SHALL BE POST TOP MOUNTED ON A 12-FOOT HIGH, STEEL POLE. LIGHT FIXTURE SHALL HAVE 0-10V DIMMING DRIVER. CONTRACTOR TO COORDINATE FITTER ADAPTER.	40	20
S13		EVERGREEN #104340L-40LED-3000K-DIM POLE: MILLERBEND BEMIDJI #DBA-E-070-120-PT1-H	LED	4,000 LUMEN, LED FIXTURE WET RATED. FIXTURES SHALL BE POST TOP MOUNTED ON A 12-FOOT HIGH, STEEL POLE. LIGHT FIXTURE SHALL HAVE 0-10V DIMMING DRIVER. CONTRACTOR TO COORDINATE FITTER ADAPTER.	40	20
S14		COOPER OR EQUAL GARDCO ECOFORM (1) FIXTURES AT 180 DEGREES APART  #GLEON-SA6B-740-U-T4FT-EA-AHD145-MS/DIM-L40W (THIS LIGHT SHALL BE FACING THE SPORT AREA)  #GLEON-SA1B-740-U-T3-EA-AHD145 (THIS LIGHT SHALL BE FACING THE PARKING LOT)	LED	ONE 249W, 44LBS, 34,384 LUMENS, POLE MOUNTED LED FIXTURE. FIXTURE SHALL HAVE AFTER HOURS DIMMING OPTION CAPABLE OF TWO NIGHTTIME MODES WITH AT LEAST 50% DIMMING AND WITH MOTION RESPONSE OVERRIDE DURING THE PROGRAMMED 50% DIMMED PERIOD. LIGHT FIXTURE SHALL HAVE PHOTOCELL. LIGHT SHALL BE FACING THE SPORT AREA, REFER TO PLANS.  ONE 44W, 33LBS, 5,986 LUMENS, POLE MOUNTED LED FIXTURE. FIXTURE SHALL HAVE AFTER HOURS DIMMING OPTION CAPABLE OF TWO NIGHTTIME MODES WITH AT LEAST 50% DIMMING. LIGHT FIXTURE SHALL HAVE PHOTOCELL. LIGHT SHALL BE FACING THE PARKING LOT, REFER TO PLANS.  FIXTURES SHALL BE MOUNTED ON A 25-FOOT HIGH, 5-INCH SQUARE STEEL POLE. FIXTURE	293	77
SCHEDULES NOTES						
1. COORDINATE ALL COLORS WITH OWNER/ARCHITECT PRIOR TO ORDERING. CONTRACTOR SHALL PROVIDE COLOR SAMPLES DURING SUBMITTAL STAGE						
2. ALL CLEAR, ACRYLIC, PRISMATIC LENSES ARE TO BE MINIMUM 0.125" PATTERN K12, U.O.N						
3. ALL LEDS SHALL HAVE A CRI OF 0.8 AND COLOR TEMPERATURE OF 4000K.						
4. ALL DRIVERS SHALL HAVE LESS THAN 10% THD.						
5. FIXTURE TYPE IS SHOWN WITHIN MOST FIXTURES.						
6. PRIOR TO ORDERING FIXTURES REFER TO THE LIGHTING PLAN FOR THE CORRECT VOLTAGES TO BE UTILIZED FOR THE FIXTURES.						
7. CONTRACTOR TO BUY (2) FSIR-100 PROGRAMMING TOOL AND GIVE THEM TO THE COUNTY AFTER LIGHTING HAS BEEN PROGRAMMED.						

 <p><b>Borrelli &amp; Associates, Inc.</b> Consulting Electrical Engineers 2032 N. Gateway Boulevard Fresno, CA 93727 Phone: 559-233-4138 <a href="http://www.borrelliengineering.com/">http://www.borrelliengineering.com/</a> <a href="mailto:co-bai@borrelliengineering.com">co-bai@borrelliengineering.com</a> BAI Project #24120</p>	 <b>SCAN ME</b>	<div><div><div><div><div></div><div></div></div><div><div></div><div></div></div></div><div><div></div><div></div></div><div><div></div><div></div></div></div><div><b>COPYRIGHT</b> Copyright 2024 by Borrelli and Associates, Inc. All rights reserved. The firm of Borrelli and Associates, Inc., and its subsidiary companies reserves its common law copyright and other applicable property rights in these plans. These plans are not to be reproduced, changed, or copied in any form or manner whatsoever, nor are they to be assigned to a third party without first obtaining the express written permission and consent of Borrelli and Associates, Inc. and its subsidiary companies. In the event of an unauthorized reuse of these plans by a third party, the third party shall hold the firm of Borrelli and Associates, Inc. and its subsidiary companies harmless and shall bear the cost of Borrelli and Associates, Inc. and its subsidiary companies legal fees associated with defending and enforcing these rights.</div></div>		<div><div><div></div><div></div></div><div><b>DATE</b></div></div>	DESCRIPTION
				<div><div><div></div><div></div></div><div><b>06-25-25</b></div></div>	CLARIFICATIONS

	DATE	RECORD DRAWING	SCALE
DESIGNED: BAI		RESIDENT ENGINEER	INDICATED ON PLANS
DRAWN: BAI		DATE	
CHECKED: JB			
FOR RIGHT OF WAY DATA AND ACCURATE ACCESS DETERMINATION, SEE DOCUMENTS IN THE DEPARTMENT OF PUBLIC WORKS AND PLANNING.			