

EQUIPMENT SCHEDULE

No.	STANDARD			VEH SIG MTG		PED SIGNAL		PPB		HPS EQUIV. LUMINAIRE WATTAGE	PG&E POLE No.	SPECIAL REQUIREMENTS
	Type	Sig. M.A.	Lum.M.A.	Mast Arm	Pole	Ø	MTG	Ø	ARROW			
A	26-4-129	45'	15'	MAS MAS	SV-2-T	=	=	=	=	78W LED (N)	XXXX	REMOVE AND SALVAGE EXISTING Ø8 VEHICLE SIGNAL HEAD, PEDESTRIAN HEAD, PPB ASSEMBLY AND LUMINAIRE. FURNISH AND INSTALL NEW Ø8 VEHICLE SIGNAL HEAD ON POLE AND LUMINAIRE ON LMA FURNISH AND INSTALL SNS "CLOVIS AVE" COMPLETE WITH MOUNTING HARDWARE ON POLE.
B	1-A (10')	=	=	=	TV-1-T	=	=	=	=	=	=	REMOVE AND SALVAGE EXISTING VEHICLE SIGNAL HEAD. FURNISH AND INSTALL NEW Ø8 VEHICLE SIGNAL HEAD.
C	1-A (10')	=	=	=	TV-3-T	=	=	=	=	=	=	REMOVE AND SALVAGE EXISTING Ø8 VEHICLE SIGNAL HEAD, PPB ASSEMBLY AND PEDESTRIAN HEAD. FURNISH AND INSTALL NEW Ø8 3-SECTION HEAD PER DETAIL O ON SHEET ED-1.
D	26-4-113	45'	15'	MAS MAS	SV-1-T	6	SP-1-T	8	LEFT	150W	XXXX	REMOVE AND SALVAGE EXISTING POLE AND ALL EQUIPMENT ATTACHED TO IT.
D'	29-5-113 (N)	50' (N)	12' (N)	(N) MAT (N) MAS _{F=17'}	SV-1-T (N)	=	=	=	=	78W LED (N)	XXXX	FURNISH AND INSTALL SNS "CLOVIS AVE" COMPLETE WITH MOUNTING HARDWARE ON POLE. FURNISH AND INSTALL PEC ON TOP OF POLE. FURNISH AND INSTALL R73-2 (MOD) "U-TURN ONLY" SIGN AND WIRELESS ANTENNA ON SMA COMPLETE WITH MOUNTING HARDWARE.
E	1-A (10')	=	=	=	TV-1-T	8	SP-1-T	6	RIGHT	=	=	REMOVE AND SALVAGE EXISTING POLE AND ALL EQUIPMENT ATTACHED TO IT.
E'	1-A (10')(N)	=	=	=	TV-1-T (N)	2 (N)	SP-1-T (N)	2 (N)	LEFT (N)	=	=	
F	19-4-113	=	15'	=	SV-2-TA	8 6	SP-2-T	8 6	RIGHT LEFT	150W	XXXX	REMOVE AND SALVAGE EXISTING POLE AND ALL EQUIPMENT ATTACHED TO IT.
F'	15TS (N)	=	12' (N)	=	SV-2-TA (N)	2 (N)	SP-1-T (N)	2 (N)	RIGHT (N)	78W LED (N)	XXXX	
G	1-A-FBS	=	=	=	TV-1-T	=	=	=	=	=	=	RELOCATE EXISTING 1-A POLE WITH MOUNTED FLASHING BEACON AND W3-3 SIGN.

- NOTES:
- ALL EQUIPMENT IS EXISTING UNLESS OTHERWISE NOTED WITH (N).
 - ALL INDICATIONS SHALL BE 12" LED MODULES.
 - STREET NAME SIGNS SHALL BE WHITE LETTERS ON GREEN BACKGROUND 12" UPPERCASE 9" LOWERCASE, 4" BLOCK NUMBERS, 4" WIDE ARROWS, SERIES "D" TEXT ON TYPE XI DIAMOND GRADE SHEETING AND 3M TYPE XI DG3 OR APPROVED EQUAL.
 - LED INTERSECTION SAFETY LIGHT LUMINAIRES INSTALLED AND SHALL BE CREE RSWS-A-HT-3ME-6L-40K7-UL-GY-N FULL POWER: 78W, 9325 LUMEN, 4000K, CRI70-B1-U0-G2, RSWS9056&SP.